

CBB61S 型金属化薄膜电容器/滤波、功率补偿 Metalized film capacitor type
CBB61S / Filtering and power compensation

特点 Characteristics

1. 金属化聚丙烯膜结构 Metallized polypropylene film structure
2. 有自愈特性 Has self-healing propertie
3. 防爆设计，更安全 Explosion-proof design, safer
4. 高稳定性，可靠性 High stability and reliability
5. 方形塑料外壳 Square plastic shel

性能指标 Specification

额定电压	Rated voltage	200~500VAC
额定电容量	capacitance	0.1 μ F~20 μ F
容量偏差	cap tolerance	$\pm 5\%$
损耗角正切	loss factor	$\leq 20 \times 10^{-4}(1V, 100Hz)$
端子间耐电压	test voltage between terminals	2.0U _n , 2s/60s
端子与外壳间耐电压	test voltage between terminals and case	(2U _n +1000)V, 60s, Not less than 2000V
运行温度（外壳）	operating temperature(case)	-40℃~+70℃、-40℃~+85℃
预期寿命（小时）	life expectancy(hours)	CLASS A（30000h） CLASS B（10000h） CLASS C（3000h）
气候类别	climate category	40/70/21、40/85/21
封装	coating	方形塑料外壳 Square plastic shell
浸渍剂	impregnant	环氧树脂 epoxy resin
引用标准	reference standard	GB/T 3667、IEC60252、UL810

客户需要特殊尺寸，请联系我们。

Please contact us if customers require special sizes.